

Akcijski katalog

01.03.2024

Slika	Naziv/Model	VPC	MPC
	Podzemni krilni motor R21/354 Set motora R21/353 sadrži: R21/351 elektromehaničk ukopni motor (2kom), FU100 celicna galvaniz. osnova (2kom) RL650 sistem otpustanja-poluge (2kom) (B70/22 sa pripadajucim,dole navedenim elementima): H70/200AC/BOX digit.kontroler za 2 motora H93/RX22A/I prijemna jedinica (1kom), E80/RX52R daljinska komanda (2kom), R90/F2ES foto celije (par), Fifty lampa (1 kom), R99/C/001 znak. Brzina otvaranja do 90 ° : 19s Brzina Manevrisanje: 1,2 Rpm Max.otvar.: 105 ° (opciono : 125 °- 360 °) Zamah: 400mm Napajanje: 230AC-50Hz Snaga motora: 200W Maksimalni potisak: 300N m Termalna zaštita motora: 150 °C Radna temperatura: -20 - 55 °C Nivo zaštite: IP67 Max. dimenzija proizvoda u mm: 345x224x144 Za krilne kapije sa krilom do 3,5m Mehaničko zaustavljanje. Napijni kabal 2m.	98330	117996.00
	KIT NVR 32 NVR5232-4KS2+32xIPC-HFW2421S-S-0280 4MP IR Fixed-focal Bullet WizSense Network Camera > 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. > Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps. > H.265 codec, high compression rate, ultra-low bit rate. > Built-in IR LED, and the max. illumination distance is 30 m. > ROI, SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments. > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. > Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human) > Supports max. 256 G Micro SD card; built in MIC. > 12 VDC/PoE power supply	262320	314784.00
	KIT NVR 16 NVR4116HS-4KS3+16xIPC-HFW2421S-S-0280 4MP IR Fixed-focal Bullet WizSense Network Camera > 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. > Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps. > H.265 codec, high compression rate, ultra-low bit rate. > Built-in IR LED, and the max. illumination distance is 30 m. > ROI, SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments. > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. > Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human) > Supports max. 256 G Micro SD card; built in MIC. > 12 VDC/PoE power supply	138260	165912.00

ZADNJI KOMAD



Integrated Mount Tester PFM906-EP

- > Supports IPC, HDCVI, AHD, HDTVI, CVBS and SDI monitor video display.
- > HDMI input and output.
- > 12 VDC 2A and USB 5V 2A output.
- > 7-in 1080p HD full-angle retina capacitive IPS touchscreen.
- > TDR network cable test and cable tracker function.
- > Optical power meter function.

80682 96818.40

DO PRODAJE ZALIHA

59380 71256.00

Access Standalone ASI2201H-W



- > PC + ABS, suitable for indoor and outdoor use.
- > 2.4" LCD screen with a resolution of 240 × 320.
- > Operating temperature: -30 °C to +65 °C (-22 °F to +149 °F).
- > IP65 rated (silicone sealant is needed, see Quick Start Guide).
- > Option to switch between reader and controller mode for added convenience.
- > 30,000 users, 30,000 cards, 30,000 passwords, 50 admin accounts, and 150,000 records.
- > Card/remote/password unlock and unlock through their combinations.
- > **IC card, ID card and NFC technology.**
- > Brand-new design with a slim, elegant structure.
- > Supports access control security module expansion to avoid tampering, increasing access safety.
- > Supports duress alarm, tamper alarm, intrusion alarm, door contact timeout alarm, illegal card exceeding threshold alarm, illegal password exceeding threshold alarm and external alarm.
- > Supports guest users, patrol users, blocklist users, VIP users, general users, and others.
- > TCP/IP and Wi-Fi communication; auto registration, P2P registration, and DHCP.
- > Supports PC/mobile web client.
- > Supports online update and USB update.
- > Doorbell function.
- > Audio prompts.
- > Compatible with SmartPSS-AC and DSS Pro.

25228.00 30273.60

12110.00 14532.00

RG59 bez napajanja 100m



2050.00 2460.00

HAC-HDW1800M + DOZNA PFA13A-E



- 4K Real-time HDCVI IR Eyeball Camera
- > Max. 4K resolution, real-time video transmission
- > CVI/CVBS/AHD/TVI switchable
- > Fixed lens (2.8mm; 3.6mm; 6mm optional)
- > Max. IR length 30m, Smart IR
- > IP67, 12V±30%DC

DO PRODAJE ZALIHA

3930.00 4716.00

PFM920I-6UN-C



- UTP CAT6 Cable
- > 305 m (1000 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable
- > High-purity oxygen-free copper conductor
- > Customized PVC outer sheath; CE CPR Eca flame retardant class certified
- > 10-year warranty

DO PRODAJE ZALIHA

10996.00 13195.20



ASI7213X-T1

Face Recognition Access Controller

- > 2.5D curved screen
- > 7-inch LCD display with resolution of 1024 × 600
- > 2MP CMOS, WDR
- > Auto illumination reduces light pollution
- > Can hold 100,000 users, 100,000 face images, 100,000 cards, 100,000 password, 50 administrators, and 300,000 records
- > Support face, IC card, password unlock and unlock through their combinations
- > With face detection box; the largest face among faces that appear at the same time is recognized first; the maximum face size can be configured on the web
- > Face-camera distance: 0.3 m–2.0 m; human height: 0.9 m–2.4 m (lens-ground distance: 1.4 m)
- > With face recognition algorithm, the terminal can recognize more than 360 positions on human face
- > Face recognition speed: 0.2 s per face
- > Support liveness detection
- > Accurate recognition in backlight and front light
- > Various unlock status display modes protect user privacy

133500.00 160200.00



ASI1212D

Fingerprint Standalone

- > Touch keyboard and LCD display
- > Support 30,000 valid cards & 150,000 records
- > Support multiple cards(default IC card) ("D" means ID EM card)
- > Support card, password, fingerprint and combination
- > TCP/IP to PC
- > Support P2P add device
- > Wiegand or RS-485 interface to reader
- > Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- > Anti-passback, multi-card open
- > Support 128 efficient time and holiday schedules
- > USB import/export configuration or log file;

REZERVISANO

13670.00 16404.00



POGODNO ZA VELIKE SISTEME

PL10PED M/Z modul .
Bez pozivnih mesta

- + PRS6220 Napajanje 40V
- + PL72

TD6100PL Digitalni
pozivni tablo PROFILO

Digitalna tastatura sa aluminijumskom prednjom pločom i 14 tastera od nerđajućeg čelika. Opremljen LCD grafičkim displejom, omogućava pozivanje kucanjem odgovarajućeg broja i otvaranje vrata pomoću koda. Integriše elektronski indeks. Može da sadrži do 250 imena korisnika.

37,300.00 44,760.00



Audio interfon za 2 korisnika
sa ID čitačem SUPER
STRONG 2

7200.00 8640.00



Audio interfon za 1
korisnika sa ID čitačem
SUPER STRONG 1

5520.00 6624.00



Bežični interfon sa
telefonom INTERDECT

11200.00 13440.00



ITF sistem za 2 korisnika "2 CKD" ili "2CKSD"
Omogućava dvosmernu komunikaciju.
Na slušalici je taster za otvaranje vrata.
Italijanski dizajn u blister pakovanju sa šemom.
Za povezivanje po sistemu "uradi sam." Slušalice u KIT-u su EX311. SISTEM
POVEZIVANJA 1+n

6405.00 7686.00



ITF sistem za 1 korisnika "1 CKD" ili "1CKSD".
Omogućava dvosmernu komunikaciju.
Na slušalici je taster za otvaranje vrata.
Italijanski dizajn u blister pakovanju sa šemom.
Za povezivanje po sistemu "uradi sam." Slušalice u KIT-u su EX311. SISTEM
POVEZIVANJA 1+n

5200.00 6240.00



UPS HOKUS PLUS 2000 1200W
Osnovne karakteristike
Tip: UPS (Uninterruptible Power Supply)
Režim rada: Line interactive
Snaga (VA): 2.000
Snaga (W): 1.200
Baterija
Broj baterija: 2
Voltaža: 12V
Kapacitet: 9Ah
Priključci / Slotovi
Izlazni priključci: 4x šuko
Povezivost: USB (Tip B)
Ostali priključci / Slotovi: 2x RJ-45/11
Zaštita Vrsta zaštite: Telefonska (modemska) zaštita, Zaštita od prevelikog opterećenja (napona)
Ostale karakteristike Dodatne funkcije: "Hladan start", Boost and buck automatska stabilizacija napona, Simulated sine wave
Displej: LCD color touchscreen
Fizičke karakteristike Dimenzije: 320mm x 182mm x 130mm
Boja: Crna

DO PRODAJE ZALIHA

17040.00 20448.00