



Switches

	<p>PFS3005-4P-58 PoE 4-portni switch; 1x 10/100 Base-T; 4x 10/100 Base-T (PoE); Do 30W po portu ili maksimalno 58W ukupno(za sve portove); PoE protokol IEEE802.3af i IEEE802.3at; MAC auto study and aging, Broj MAC adresa 1K; Default i Extended mod rada.Default je kao standarni switch,dok se u Extended modu PoE portovi se ponašaju kao 10Mbps portovi sa dometom do 250m ; Napajanje DC51V priloženo uz uređaj; Radna temperatura od 10°C~50°C; Dimenzije 100mm×100mm×26mm; Masa uređaja 259g</p>	50,00	60,00
	<p>PFS3005-5GT-L 5 ports 10/100/1000Mbps</p>	13,00	15,60
	<p>PFS3005-4ET-60-V2 4 portni POE neupravljivi svic, podrzava POE power management, podrzava 4 POE porta 10/100Mbps + 1 uplink port 100 Mbps</p>	54,00	64,80
	<p>PFS3006-4GT-60 6 portni (4POE), neupravljivi gigabitni svic, 1 port podrzava HI-POE (60W), podrzava 4 POE porta 10/100/1000 Mbps + 2 uplink porta 10/100/1000 Mbps</p>	76,00	91,20
	<p>PFS3110-8ET-96 PoE 8-portni switch industrijski; 1x100/1000 Base-x ;1x10/100/1000 Base-T; 8x10/100 Base-T (PoE); Do 30w po portu ili maksimalno 96w (ukupno za sve portove) poebno podesavanje potrosnje za svaki port; PoE protokol IEEE 802.3afi IEEE 802.3at;, Broj MAC adresa 8K; Napajanje DC53V prilozeno uz uređaj; Radna temperatura od -30°C do 65°C; Dimenzije 150mm×100mm×42mm; Masa uređaja 540g Podrzava sledece SFP module: PFT3950 1.25G 850nm,500m,LC, Multi-mode PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	143,00	171,60
	<p>PFS3010-8GT-96 10-portni gigabitni neupravljivi svic, 8 POE portova, podrzava IEEE802.3bt I HI POE standarde, maksimalna snaga je 90W po portu.</p>	149,00	178,80

	<p>PFS3009-8ET-96 Poe 8-portni switch, 1x10/100 Base-T, 8x10/100, Do 60W po portu maksimalno potr 1. PoE protokol IEEE802.3af i IEEE802. Dimenzije 190mm×100mm×30mm. Radna temperatura - 10°C~+55°C. Napajanje DC48~57V power adapter.</p>	86,00	103,20
	<p>PFS3008-8GT-60 8-portni gigabitni PoE switch 8 x10/100/1000M Base- T (PoE power supply) 4x 10/100/1000M Base-T (PoE power supply) 4x 10/100/1000M Base-T; Port1≤60W, Port2- 4≤30W, Total≤60W IEEE802.3af/IEEE802.3at/Hi- PoE Power supply:DC48~57V Dimenzije: 190mm×100mm×30mm Masa: 480g</p>	60,00	72,00
	<p>PFS3008-8GT-96 8-portni gigabitni PoE switch 8 x10/100/1000M Base-T (PoE power supply) Port1≤60W, Port2-8≤30W, Total≤96W IEEE802.3af/IEEE802.3at/Hi-PoE Power supply:DC48~57V Dimenzije: 190mm×100mm×30mm Masa: 480g Podrjava sledece SFP module: PFT3950 1.25G 850nm,500m,LC, Multi-mode PFT3960 1.25G 1310/1550nm,20km,LC, Single- mode PFT3970 1.25G 1550/1310nm,20km,LC, Single- mode</p>	108,00	129,60
	<p>PFS3008-8GT-L 8 ports 10/100/1000Mbps</p>	16,00	19,20
	<p>PFS3008-8GT 8-Port Unmanaged Desktop Gigabit Switch, Layer 2 unmanaged access switch, All gigabit ethernet ports Lightning protection, Plug and play, Adopts metal enclosure, Good heat dissipation</p>	22,00	26,40
	<p>PFS3009-8ET1GT-96 Port Unmanaged Desktop Swith sa 8 Port PoE Intelligentni PoE BT 90V 8-pin dodeljivanje PoE napajanja PoE na daljinu PoE čuvar Široka radna temperatura</p>	65,00	78,00
	<p>PFS4018-16P-250 16-portni upravljivi POE switch, 2*10/100/1000 Base-T 16*10/100 Base-T(PoE power supply), ukupan POE budyet 250W,</p>	488,00	585,60
	<p>PFS4218-16ET-240 Upravljivi svic sa 16 x 100mbps POE portova i 2 x gigabit POE porta, inteligent POE, 240W ukupno, 250m POE distanca, POE watchdog, plug&play,</p>	363,00	435,60

	<p>PFS4218-16ET-190 16-portni PoE switch; 2x10/100/1000 Base-T (Combo); 2x1000 Base-X (Combo); 16x10/100 Base-T (PoE); Do 60W po portu ili maksimalno 190W (Ukupno za sve kanale) ; PoE protokol IEEE 802.3af, IEEE 802.3ati Hi PoE; Switching Capacity 8.8G; Packet Forwarding Rate 6.66 Mpps; Spanning tree protocol STP/RSTP; Napajanje 220V Ac; Radna temperatura od -10°C do 55°C; Dimenzije 440mmx300mmx44mm; Masa 3.51g Podrjava sledece SFP module: PFT3950 1.25G 850nm,500m,LC, Multi-mode PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	273,00	327,60
	<p>DH-PFS3226-24ET-240 Neupravljivi switch sa 24 POE porta, dual port uplink 100mbps, plug & play, HI-POE, optimalna radna distanca 250m.</p>	294,00	352,80
	<p>PFS3228-24GT-360 Neupravljani PoE switch sa crvenim portom podrjava standard IEEE802.3bt. Podrjava maksimalnu snagu od 90V Obezbeđuje stabilan rad u ekstremnim uslovima. Gigabitni pristupi održavaju visoku brzinu. Gigabit uplink optičko vlakno podrjava dug prenos na daljinu. - Intelligent PoE · Crveni port podrjava BT 90V · Svi giga- portovi · Glatki prenos · Široka radna temperatura: -10°C do 55°C (14°F do 131°F) · Plug and Play</p>	498,00	597,60
	<p>PFS4226-24ET-240 24 portni industrijski POE switch 2*10/100/1000 Base-T (Combo port), 2*1000 Base-X (Combo port), 24*10/100 Base-T (PoE napajanje), svaki izlaz ≤30W, Ukupno ≤360W, Port 1/2 podrjava Hi-PoE (60W), PoE+, PoE, PoE protokol: IEEE802.3af, IEEE802.3at, Hi-PoE, PoE transmisija do 250m, Radna temperatura: -10°C~55°C, Dimenzije:440mm×300mm×44mm Podrjava sledece SFP module: PFT3950 1.25G 850nm,500m,LC, Multi-mode PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	344,00	412,80

	<p>PFS4226-24ET-360 24 portni industrijski POE switch 2*10/100/1000 Base-T (Combo port), 2*1000 Base-X (Combo port), 24*10/100 Base-T (PoE napajanje), svaki izlaz ≤30W, Ukupno ≤360W, Port 1/2 podržava Hi-PoE (60W), PoE+, PoE, PoE protokol: IEEE802.3af, IEEE802.3at, Hi-PoE, PoE transmisija do 250m, Radna temperatura: -10°C~55°C, Dimenzije:440mm×300mm×44mm Podržava sledece SFP module: PFT3950 1.25G 850nm,500m,LC, Multi-mode PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	446,00	535,20
	PFT3950 1.25G 850nm,500m,LC, Multi-mode	48,00	57,60
	PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode	50,00	60,00
	PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode	76,00	91,20