















DAHUA KONTROLA PRISTUPA

	<p>Dahua ASC 1202B-D Kontroler kontrole pristupa za dvoje vrata (4 čitača), dvosmerni, podržava 100.000 kartica, 150.000 zapisa, TCP/IP port, podržava čitače kartica, otiska prsta, šifre ili kombinaciju, wiegand ili 485 konekcija sa čitačima. Ulazi x8 od toga 2 za senzore vrata, 2 za izlazne tastere i 4 alarmna izlaza. Izlaznih releja x6 od toga 2 za bravu i 4 alarmna izlaza. Napajanje 9-15VDC, 500mA</p>		124,00	148,80
	<p>ASC 1204C-D Kontroler kontrole pristupa za cetiri vrata (two way), podrzava 100,000 kartica, 150,000 zapisa, Podrzava kartice, sifre, otisak prsta ili kombinaciju, TCP/IP interface, Wiegand ili RS-485 interface za konekciju citaca Anti-pass back, multi-door interlock, multi-card open, Support 128 efficient time, podrzava baterijsko napajanje</p>		424,00	508,80
	<p>Dahua ASR 1200D Vodo otporni čitač kartica Mifare</p>		46,00	55,20
	<p>ASI1201A RFID (125khz) standalone citac kartica, podrzava 30.000 kartica I 150.000 dogadjaja, podrzava citanje kartica, kucanje sifre ili kombinaciju, TCP/IP komunikacija, wiegand, RS485, antipass back,</p>		117,00	140,40
	<p>ASI1212D MIFARE Standalone citac otiska prsta i citac kartica, touch tastatura I LCD displej, podrzava 30.000 kartica I 150.000 zapisa, TCP/IP, podrzava P2P, wiegand, RS485, USB import/export, anti pass back funkcija.</p>		247,00	296,40
	<p>Dahua IC S50 Mifare Dahua kartica</p>		1,00	1,20



ASI7213X-T1

Kontroler za kontrolu pristupa sa prepoznavanjem lica, 7" LCD displej rezolucije 1024x600, 2MP kamera sa WDR-om, automatska regulacija osvetljaja, podrzava 100.000 korisnika, 100.000 skeniranih lica, 100.000 kartica, 100.000 sifri, 50 administratora i 300.000 zapisa, brzina prepoznavanja lica 0.2s po licu, podrzava ukljucenje/iskljucenje funkcije merenja temperature, temperaturni raspon je 30-45 stepeni, distanca merenja temperature je 0.3m-1.8m, alarmiranje prilikom abnormalne izmerene temperature, obavestavanje o licu koje ne nosi masku, montaza na zid ili stalak.

Video:

https://www.youtube.com/watch?v=1pPfcUZqYkg&feature=emb_logo



2500,00 3000,00